

2009 Town & Country

Models: DIMENSIONS & CAPACITIES







	TOWN & COUNTRY LX Change Vehicle	TOWN & COUNTRY TOURING Change Vehicle	Change Vehicle	Change Vehicle
ISRP	\$27,250	\$30,215	\$33,735	\$37,350
xterior Dimensions	φ2 <i>1</i> ,250	\$30,218	\$33,735	\$37,35U
round Clearance - at curb weight - unning Ground Clearance	6.1"	6.1"	6.1"	6.1"
verall Height - With Roof Rack	71.4"	71.4"	71.4"	71.4"
verall Height - Without Roof Rack	68.9"	68.9"	68.9"	68.9"
verall Length	202.5"	202.5"	202.5"	202.5"
verall Width	76.9"	76.9"	76.9"	76.9"
verhang - Front	37.6"	37.6"	37.6"	37.6"
verhang - Rear	43.7"	43.7"	43.7"	43.7"
rack - Front	65.5"	65.5"	65.5"	65.5"
rack - Rear	64.8"	64.8"	64.8"	64.8"
urning Diameter - curb-to-curb - Left	38.0'	38.0'	38.0'	38.0'
urning Diameter - curb-to-curb - ight	38.0'	38.0'	38.0'	38.0'
/heelbase(i)	121.2"	121.2"	121.2"	121.2"
nterior Dimensions				
argo Capacity - Behind 2nd Row eat	82.7ft ³	83.7ft ³	83.7ft ³	83.7ft ³
argo Capacity - Behind 3rd Row eat	32.3ft ³	32.3ft ³	32.3ft ³	32.3ft ³
argo Capacity - Behind Front Seat	143.8ft ³	140.1ft ³	140.1ft ³	140.1ft ³
ead Room - Front	39.8"	39.8"	39.8"	39.8"
ead Room - Second Row	39.2"	39.7"	39.7"	39.7"
ead Room - Third Row	37.9"	37.9"	37.9"	37.9"
p Room - 3rd Row	48.7"	48.7"	48.7"	48.7"
ip Room - Front	57.6"	57.6"	57.6"	57.6"
p Room - Second Row	64.8"	64.8"	64.8"	64.8"
eg Room - Front	40.6"	40.6"	40.6"	40.6"
eg Room - Second Row	36.4"	36.3"	36.3"	36.3"
eg Room - Third Row	37.6"	31.8"	31.8"	31.8"
assenger Interior Volume	163.5ft ³	156.1ft ³	156.1ft ³	156.1ft ³
eating Capacity - Maximum Seating	7	7	7	7
eating Capacity - Standard Seating	7	7	7	7
houlder Room - Front	63.0"	63.0"	63.0"	63.0"
houlder Room - Second Row	64.7"	64.7"	64.7"	64.7"
houlder Room - Third Row	62.0"	62.0"	62.0"	62.0"
runk lift over height	24.4"	24.4"	24.4"	24.4"
apacities/Weights				
ase Curb Weight - Automatic Trans	4335lbs.	4507lbs.	4507lbs.	4621lbs.
uel Tank Capacity	20.5gal.	20.5gal.	20.5gal.	20.5gal.
ross Vehicle Weight Rating (GVWR)	6050	6050	6050	6050
yload Capacity	1200	1200	1200	1200
owing Capacity - Maximum	1800lbs.	3600lbs.	3600lbs.	3600lbs.
owing Capacity - Standard	1600lbs.	1600lbs.	1600lbs.	1600lbs.
leight Distribution - Automatic Trans Front	56.0%	56.0%	56.0%	56.0%
/eight Distribution - Automatic Trans Rear	44.0%	44.0%	44.0%	44.0%
asics				
akes - Front	Disc	Disc	Disc	Disc

Brakes - Rear	Disc	Disc	Disc	Disc
Driveline Configuration	FWD	FWD	FWD	FWD
EPA Classification	Mini Van (2WD)	Mini Van (2WD)	Mini Van (2WD)	Mini Van (2WD)
Maximum Number of Doors	4	4	4	4
Standard Number of Doors	4	4	4	4
Steering	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
Suspension - Front	Independent	Independent	Independent	Independent
Suspension - Rear	Twist Beam	Twist Beam	Twist Beam	Twist Beam
Tires - Aspect Ratio	65	65	65	65
Tires - Construction	R	R	R	R
Tires - Spare Tire Type (Full / Compact)	Compact	Compact	Compact	Compact
Tires - Type	Р	Р	Р	Р
Tires - Wheel Diameter	16"	16"	16"	17"
Tires - Width	225	255	255	225
Tops - Standard Top	HardTop	HardTop	HardTop	HardTop
Vehicle Type	Passenger Van	Passenger Van	Passenger Van	Passenger Van
	BUILD MY OWN	BUILD MY OWN	BUILD MY OWN	BUILD MY OWN
	GET A QUOTE	GET A QUOTE	GET A QUOTE	GET A QUOTE
	COMPARE TO COMPETITION	COMPARE TO COMPETITION	COMPARE TO COMPETITION	COMPARE TO COMPETITION

Important Disclosure Information