

MSRP	XF	XF	XF
	Luxury	Premium Luxury	Supercharged
Manufacturer's Suggested Retail Price <sup>1</sup>	\$49,975.00	\$55,975.00	\$64,475.00

Engine	XF Luxury	XF Premium Luxury	XF Supercharged
Туре	DOHC	DOHC	DOHC
Cam phasing	Variable	Variable	Variable
Construction	Aluminum alloy cylinder head/block	Aluminum alloy cylinder head/block	Aluminum alloy cylinder head/block
Cylinders	90-degree V8	90-degree V8	90-degree V8 S/C
Valves per cylinder	4	4	4
Bore	3.39 in.	3.39 in.	3.39 in.
Stroke	3.56 in.	3.56 in.	3.56 in.
Displacement	4.2 liter	4.2 liter	4.2 liter
Compression ratio	11.0:1	11.0:1	9.1:1
Induction	Naturally aspirated	Naturally aspirated	Supercharged and intercooled

Horsepower (SAE)	300 bhp @ 6,000 rpm	300 bhp @ 6,000 rpm	420 bhp @ 6,250 rpm
Maximum torque	310 lbft. @ 4,100 rpm	310 lbft. @ 4,100 rpm	413 lbft. @ 4,000 rpm

Performance	XF Luxury	XF Premium Luxury	XF Supercharged
0-60 mph	6.2 seconds	6.2 seconds	5.1 seconds
Maximum speed (electronically limited)	121 mph	121 mph	155 mph
EPA estimated fuel economy	16 city / 25 highway	16 city / 25 highway	15 city / 23 highway

Braking	XF Luxury	XF Premium Luxury	XF Supercharged
Front	12.83 in. ventilated discs with single piston calipers	12.83 in. ventilated discs with single piston calipers	13.98 in. ventilated discs with single piston calipers/ABS
Rear	12.83 in. ventilated discs with single piston calipers	12.83 in. ventilated discs with single piston calipers	12.83 in. ventilated discs with single piston calipers/ABS

Wheels & Tires	XF Luxury	XF Premium Luxury	XF Supercharged
Wheels	18 x 8.5 in. alloy, Cygnus	19 x 8.5 in. alloy, Auriga <sup>2</sup>	20 x 8.5 in. alloy (front), 20 x 9.5 in. alloy (rear), Volans <sup>2</sup>
Tires	245/45 HR18 all season	245/40 HR19 all season	255/35 ZR20 (front) 285/30 ZR20 (rear) performance tires <sup>3</sup>

Steering	XF	XF	XF
	Luxury	Premium Luxury	Supercharged
Turning circle (curb to curb)	37.68 ft. (11.48m)	37.68 ft. (11.48m)	37.68 ft. (11.48m)
Dimensions	XF	XF	XF
	Luxury	Premium Luxury	Supercharged

Length	195.3 in.	195.3 in.	195.3 in.
Height	57.5 in.	57.5 in.	57.5 in.
Width (including mirrors)	80.8 in.	80.8 in.	80.8 in.
Wheelbase	114.5 in.	114.5 in.	114.5 in.
Curb weight	4017 lbs.	4017 lbs.	4194 lbs.
Headroom (front)	39 in.	39 in.	39 in.
Headroom (rear)	37.4 in.	37.4 in.	37.4 in.
Shoulder room (front)	56.8 in.	56.8 in.	56.8 in.
Shoulder room (rear)	56.3 in.	56.3 in.	56.3 in.
Legroom (front)	41.5 in.	41.5 in.	41.5 in.
Legroom (rear)	36.6 in.	36.6 in.	36.6 in.

Capacities	XF Luxury	XF Premium Luxury	XF Supercharged
Trunk (Useable NVMA)	17.7 cu. ft.	17.7 cu. ft.	17.7 cu. ft.
Fuel	18.4 gal.	18.4 gal.	18.4 gal.

<sup>&</sup>lt;sup>1</sup>Includes destination and delivery. Excludes taxes, title, license, emissions and other local fees. Actual dealer price may vary. Prices and specifications subject to change without notice. See your Jaguar Dealer for details on optional equipment and accessories.

http://origin-www.jaguar.com/us/en/xf/models\_pricing/specifications/specifications.htm

<sup>&</sup>lt;sup>2</sup>The 19-inch & 20-inch wheel and tire assembly is of low profile with a bias towards sporting attributes. Wheel and tire assemblies with low tire sidewall height will be more susceptible to impact damage in service.

<sup>&</sup>lt;sup>3</sup>This vehicle is equipped with an Ultra High performance tire and wheel combination designed to provide maximum dry pavement performance with consideration for hydroplaning resistance. As such, they may be more susceptible to road hazards, and consequential damage. Ultra high performance tires may also be expected to experience increased tread wear with shorter tread life. These tires are not recommended for driving on snow or ice, and should be replaced with winter tires when weather conditions dictate.