



SRX CROSSOVER SPECIFICATIONS

Braking

Brakes 4-wheel disc brakes with anti-lock braking system ABS and Brake Assist

Suspension & Handling

Suspension 4-wheel independent design that utilizes a short/long arm, coil-over strut with anti-sway bar in front, and a modified multi-link with anti-sway bar and automatic rear level control system in the rear; both benefit from monotube performance shock absorbers

All-Speed Traction Control All-speed, brake and engine controlled

Stability System StabiliTrak, computer-controlled, 4-channel electronic stability control system

Steering Speed-sensitive, variable-assist power rack-and-pinion

Tires & Wheels

Tires P235/65R17 front, P255/60R17 rear; H-rated all-season (Standard: V6)
 P235/60R18 front, P255/55R18 rear; V-rated all-season (Optional: V6 / Standard: V8)
 P255/50R20 front and rear; V-rated all-season (Optional: V8)*

Wheels 17 in. x 7.5 in. cast aluminum with painted finish (Standard: V6)
 17 in. x 7.5 in. cast aluminum with machine finish (Optional: V6)
 18 in. x 8 in. cast aluminum with machine finish (Optional: V6 / Standard: V8)
 20 in. cast aluminum with polished finish (Optional: V8)*

*Use only GM approved wheel and tire combinations. See dealer for details.

↑ Capacities | ↑ Powertrain | ↑ Chassis & Suspension

[Help Center](#) | [Contact Us](#) | [Search](#) | [Request a Brochure](#) | [Merchandise](#) | [Commercials & Downloads](#) | [Owner Privileges](#) | [Experience OnStar](#)

QUESTIONS? 1-800-333-4CAD

[SITE MAP](#)

[COPYRIGHT & TRADEMARK](#)

[PRIVACY STATEMENT](#)

[GM SITES](#)

[GLOBAL SITES](#)

