

2010 Callaway Camaro Specifications



Engine

- SC572 - LS3
 - 6.2 liter (378 cu.in.) V8, 90°, cast aluminum block and heads; 6-bolt cross-bolted main caps
 - Supercharger: Eaton 2300 cc Twin Vortices Series (TVS) Roots-style; with air/liquid intercooler integral to intake manifold. 44" Hg manifold pressure, absolute. (7 psig max.)
 - Bore x Stroke: 4.060 in. x 3.622 in.
 - Compression ratio: 10.7:1
 - Maximum Power: 572 bhp* @ 6400 rpm
 - Maximum Torque: 541 lb-ft* @ 4000 rpm
 - Maximum Engine Speed: 6500 rpm
 - Fuel system: Increased flow fuel injectors
 - Ignition system: coil per cylinder
 - Throttle body: 90mm diameter, drive-by-wire

*SAE test method

Suspension

- Standard - Chevrolet Camaro SS suspension system
- Optional - Callaway Coil-Over suspension system, with non-adjustable dampers
 - double adjustable machined aluminum dampers
 - nitrogen-over-oil pressurization
 - Callaway anti-roll bars, tubular steel, front and rear
- Optional - Callaway Coil-Over suspension system, with double-adjustable dampers
 - double adjustable machined aluminum dampers
 - nitrogen-over-oil pressurization
 - independent compression and rebound damping; externally adjustable
 - Callaway anti-roll bars, tubular steel, front and rear

Wheels & Tires

- Standard -
 - Front: Choice of original equipment 20 x 8 aluminum wheels; 245/45ZR20 original equipment tires
 - Rear: Choice of original equipment 20 x 9 aluminum wheels; 275/40ZR20 original equipment tires
- Optional -
 - Front: Callaway 9 Spoke Alloy 20 x 8 wheels; 245/45ZR20 original equipment tires
 - Rear: Callaway 9 Spoke Alloy 20 x 9 wheels; 275/40ZR20 original equipment tires

Brakes

- Standard -
 - 4-wheel anti-lock, 4-wheel disc brake system with four-piston calipers
- Optional -
 - Callaway Le Mans GT 6-piston (front) and 4-piston (rear) calipers with 355 x 32 mm rotors (front & rear)

Dimensions

- Wheelbase: 112.3 inches
- Track: front - 63.7 inches; rear - 63.7 inches
- Overall Height: 54.2 inches
- Overall Length: 190.4 inches
- Overall Width: 75.5 inches (without mirrors)
- Curb weight: 3897 pounds, w/1/2 fuel, Callaway wheels, Le Mans GT brakes
- Fuel capacity: 19 gallons

Fuel Economy

- Est. Fuel Economy - City: 15 mpg
- Est. Fuel Economy - Highway: 23 mpg

Warranty

Vehicle/Powertrain: GM vehicle and powertrain warranties apply with supplemental 3 year/36,000 mile warranty on Callaway powertrain components; Callaway 3 year/36,000 mile "bumper-to-bumper" warranty (on non-powertrain related components). Callaway warranty also covers specific GM engine parts compromised by failure of Callaway components.

Performance Data

2010 Callaway Camaro	SC572 coupe, w/man trans
0-60 mph, seconds*	3.9
1/4 mile elapsed time & speed*	11.94 sec @ 119.5 mph

*Acceleration testing conducted with performance tires.

Callaway Cars reserves the right to change product specifications and availability without notice.

CALLAWAY CARS INCORPORATED

CORONA CALIFORNIA 951 279 0400 | OLD LYME CONNECTICUT 860 434 9002 | LEINGARTEN GERMANY +49 7131 9031-0