

**S** = STANDARD **O** = OPTIONAL **-** = NOT APPLICABLE

[Collapse All](#)

	LX V6	LX V8	EX V6	EX V8	LTD
<b>ENGINE &amp; TRANSMISSION</b>					
Engine Type: V6, Aluminum Block and Heads	S	-	S	-	-
Engine Type: V8, Aluminum Block and Heads	-	S	-	S	S
Displacement: 3.8L	S	-	S	-	-
Displacement: 4.0L	-	S	-	S	S
Horsepower (SAE net): 276 hp @ 6,000 rpm	S	-	S	-	-
Horsepower (SAE net): 337 hp @ 6,000 rpm	-	S	-	S	S
Torque (SAE net): 267 ft. lbs. @ 4,400 rpm	S	-	S	-	-
Torque (SAE net): 323 ft. lbs. @ 3,500 rpm	-	S	-	S	S
Transmission: Electronically Controlled 5-Speed Automatic, Overdrive	S	-	S	-	-
Transmission: Electronically Controlled 6-Speed Automatic, Overdrive	-	S	-	S	S
<b>EPA FUEL ECONOMY</b>					
Estimated MPG (City/Hwy) (2WD)	17/21	15/22	17/21	15/22	15/22
Estimated MPG (City/Hwy) (4WD)	16/21	15/20	16/21	15/20	15/20
Fuel Tank Capacity (Gallons)	20.6	20.6	20.6	20.6	20.6
<b>EXTERIOR DIMENSIONS</b>					
Wheelbase: 114.0 in.	S	S	S	S	S
Track: (Front/Rear): 17" Tires: 64.2/64.6 inches	S	-	S	-	-
Track: (Front/Rear): 18" Tires: 83.6/84.0 inches	-	S	O	S	S
Length: 192.3 in.	S	S	S	S	S
Width: 75.4 in.	S	S	S	S	S
Height: 71.3 in. (w/roof rails)	S	S	S	S	S
Ground Clearance: 8.5 in.	S	S	S	S	S
Approach Angle: 27.3 degrees	S	S	S	S	S
Departure Angle: 22.5 degrees	S	S	S	S	S
<b>INTERIOR DIMENSIONS</b>					
Headroom (Front): 40.0 in.	S	S	S	S	S
Headroom (Middle): 39.0 in.	S	S	S	S	S
Headroom (Rear): 38.0 in.	S	S	S	S	S
Shoulder Room (Front): 60.2 in.	S	S	S	S	S
Shoulder Room (Middle): 59.1 in.	S	S	S	S	S
Shoulder Room (Rear): 55.7 in.	S	S	S	S	S
Legroom (Front): 41.7 in.	S	S	S	S	S
Legroom (Middle): 37.4 in.	S	S	S	S	S
Legroom (Rear): 32.9 in.	S	S	S	S	S
Hip Room (Front): 57.1 in.	S	S	S	S	S
Hip Room (Middle): 56.1 in.	S	S	S	S	S
Hip Room (Rear): 44.9 in.	S	S	S	S	S
Interior Volume: 156.8 in.	S	S	S	S	S
Cargo Volume: 12.4 in.	S	S	S	S	S

**CURB WEIGHT**

5-Speed Automatic (2WD)	4,248 LBS		4,248 LBS		
5-Speed Automatic (4WD)	4,460 LBS		4,460 LBS		
6-Speed Automatic (2WD)		4,405 LBS		4,405 LBS	
6-Speed Automatic (4WD)		4,621 LBS		4,621 LBS	4,621 LBS

**CAPACITIES**

Towing Capacity	5,000 LBS	7,500 LBS	5,000 LBS	7,500 LBS	7,500 LBS
-----------------	-----------	-----------	-----------	-----------	-----------

**BODY & CHASSIS**

Layout: Front Engine, Rear 2WD or 4WD	S	S	S	S	S
Body Type: Ladder Frame with 8 Crossmembers	S	S	S	S	S
Front Suspension: Double-Wishbone, Coil Springs w/Shock Absorber & Stabilizer Bar	S	S	S	S	S
Rear Suspension: Multi-Link, Coil Springs w/Damper & Stabilizer Bar	S	S	S	S	S
Steering Type: Rack-and-Pinion, Power-Assisted	S	S	S	S	S
Turning Circle: Curb-to-Curb 36.5 ft.	S	S	S	S	S

**BRAKES**

Brake Type: Dual-Diagonal, Split-Circuit, Power-Assisted, Anti-Lock Braking System w/ESC	S	S	S	S	S
Front: 12.8" Vented Discs	S	S	S	S	S
Rear: 12.8" Solid Discs	S	S	S	S	S

**TIRES**

Size: 245/70R17	S		S		
Size: 265/60R18		S	C	S	S



# 2009 Kia Borrego SPECIFICATIONS

## DISCLAIMER

Kia Motors America reserves the right to make changes at any time without notice, and without incurring any obligations as to colors, materials, specifications, features, options, accessories, and packages. Some vehicles shown may include optional equipment. Kia Motors America, by the publications and dissemination of this web site, does not create any warranties, express or implied, to any Kia product. See dealer for details.