

OPEN MENU

HOME

SOUND OFF

Exterior Dimensions

Overall length	177.1 in. (4,500 mm)
Wheelbase	104.7 in. (2,660 mm)
Body width (inc. mirrors)	85.7 in. (2,180 mm)
Body width (exc. mirrors)	75.1 in. (1,910 mm)
Track, front	63.0 in. (1,601 mm)
Overall height (exc. GPS antenna)	68.5 in. (1,740 mm)
Overall height (inc. GPS antenna)	69.5 in. (1,765 mm)

Interior Dimensions

Seating capacity	5
Headroom, front/rear	40.2/39.4 in. (1,020/1,000 mm)
Legroom, front/rear	41.9/36.4 in. (1,065/925 mm)
Shoulder room, front/rear	57.6/57.3 in. (1,465/1,460 mm)
Cargo capacity	
Rear seat folded	58.9 cu. ft. (1.67 m ³)
Behind rear seat	26.7 cu. ft. (0.76 m ³)
Loadspace length	
Behind rear seat	36.0 in. (915 mm)
Maximum	61.8 in. (1,570 mm)
Maximum loadspace width	
Between wheel arches	39.5 in. (1,000 mm)
Maximum width	49.1 in. (1,245 mm)
Maximum loadspace height	34.8 in. (885 mm)

**Images of vehicle may show optional equipment.

KEEP ME INFORMED

REQUEST A BROCHURE

CONTACT A RETAILER

PAYLOAD & TOWING CAPACITY / ANGLES & CLEARANCES

Payload & Towing Capacity	Curb weight	4,255 lb. (1,930 kg)
	Gross Vehicle Weight Rating (GVWR)	5,520 lb. (2,505 kg)
	Maximum payload	1,100 lb. (500 kg)
	Maximum roof-rack load	165 lb. (75 kg)
	Maximum trailer weights	
	Trailers without brakes	1,650 lb. (750 kg)
	Trailers with brakes	3,500 lb. (1,585 kg)
	Maximum tongue weight	330 lb. (150 kg)

Angles & Clearances	Ground Clearance	8.3 in. (210 mm)
	Wading Depth	19.7 in. (500 mm)
	Angle of approach	29 degrees (SAE)
	Angle of departure	32 degrees (SAE)
	Ramp breakover angle	21.5 degrees (SAE excluded angle)
	Ascent/descent	30 degrees (continuous)
		45 degrees (drive-through)

STEERING / ENGINE

Steering	Type	Power-assist rack-and-pinion
	Turns lock-to-lock	2.6