

OPEN MENU

SOUND OFF

Exterior Dimensions

Overall Width	75.4 in. (1915 mm) body width. 86.2 in. (2190 mm) with mirrors.
Overall Body Length	190.9 in. (4848 mm), includes license-plate plinth
Track, Front	63.2 in. (1605 mm)
Overall Body Height	74.5 in. (6 ft. 2.5 in./1891 mm) *
Wheelbase	113.6 in. (2885 mm)
Track, Rear	63.5 in. (1613 mm)

Interior Dimensions

Seating capacity	Seven
Head room, front/second row	40.4/42.4 in. (1027/1076 mm)
Head room, third row	40.1 in. (1018 mm)
Leg room, front/second row	42.4/37.6 in. (1078/955 mm)
Leg room, third row	36.3 in. (923 mm)
Shoulder room, front/second row	59.2/59.4 in. (1503/1508 mm)
Shoulder room, third row	42.8 in. (1087 mm)
Cargo capacities	
All seats folded	90.3 cu. ft. (2.56 m3)
Behind second-row seat	44.5 cu. ft. (1.26 m3)
Behind third-row seat	9.9 cu. ft. (.28 m3)
Max. loadspace length	76.8 in. (1950 mm)
Max. loadspace width	
Between wheel arches	45.1 in. (1146 mm)
Maximum width	48.6 in. (1235 mm)

\* Including roof rails, with Electronic Air Suspension (EAS) in Standard mode

\*\*Images of vehicle may show optional equipment.

KEEP ME INFORMED

REQUEST A BROCHURE

CONTACT A RETAILER

## PAYLOAD & TOWING CAPACITY / ANGLES & CLEARANCES

Payload & Towing Capacity	Curb weight	5,796 lb. (2629 kg)
	Gross Vehicle Weight Rating (GVWR)	7,121 lb. (3230 kg)
	Maximum payload	1,325 lb. (601 kg)
	Maximum roof-rack load	165 lb. (75 kg)
	Maximum trailer weights	
	Trailers without brakes	1,654 lb. (750 kg)
	Trailers with brakes	7,716 lb. (3500 kg)
	Maximum tongue weight	551 lb. (250 kg)

Angles & Clearances	Minimum Ground Clearance	7.3 in. (185 mm) in Standard mode 9.5 in. (240 mm) in Off-Road mode
	Maximum Gradients	
	Angle of approach	32.2-37.2 degrees*
	Angle of departure	24.9-29.6 degrees*
	Ramp breakover angle	22.8-27.9 degrees* (excluded angle)
	Ascent/Descent	45/45 degrees drive-through 35/35 degrees continuous
	Side slope	35 degrees continuous
	Maximum Wading Depth	27.6 in. (700 mm)*

\* Figures represent the range with EAS in Standard mode and in Off-Road mode, except for wading depth, where EAS is in Off-Road mode only.

## STEERING / ENGINE

Steering	Type	Power-assisted rack-and-pinion
	Turns lock-to-lock	3.3