



Overall body length	188.5 in. (4,788 mm)	
Wheelbase	108.0 in. (2,745 mm)	
Body width (inc. mirrors)	85.4 in. (2,170 mm)	
Body width (exc. mirrors)	75.9 in. (1,928 mm)	
Max. height	71.5 in. (5 ft. 11.5 in./1,817 mm)*	
Track (front)	63.2 in. (1,605 mm)	
Track (rear)	63.5 in. (1,612 mm)	
Minimum ground clearance	8.9 in. (227 mm) in Off-road mode 6.8 in. (172 mm) in Standard mode	
Cargo volume	71.0 cu. ft. (2.01m3)	
Maximum wading depth	27.6 in. (700 mm)**	
Angle of approach	34 degrees**	
Ramp breakover angle	25 degrees**	
Angle of departure	29 degrees**	

## **INTERIOR DIMENSIONS**

Seating capacity	Five
Headroom, front/rear	39.4/38.4 in. (1,000/975 mm)
Legroom, front/rear	39.1/37.6 in. (992/955 mm)
Shoulder room, front/rear	59.0/58.2 in. (1,498/1,478 mm)

<sup>\*</sup>In Standard mode. \*\*In Off-road mode. Angle of departure for Supercharged: 27 degrees.

KEEP ME INFORMED | REQUEST A BROCHURE | CONTACT A RETAILER

Minimum ground clearance	8.9 in. (227 mm) in Off-road mode 6.8 in. (172 mm) in Standard mode
Cargo volume	71.0 cu. ft. (2.01m3)
Maximum wading depth	27.6 in. (700 mm)*
Angle of approach	34 degrees*
Ramp breakover angle	25 degrees*
Angle of departure	29 degrees*

Feature	V8 HSE	V8 SUPERCHARGED
Curb weight	5,468–5,702 lb. (2,480–2,586 kg)	5,671–5,764 lb. (2,572–2,614 kg)
	6,769 lb. (3,070 kg	) 6,890 lb. (3,125 kg)
	1,067–1,301 lb. (484–590 kg)	1,126–1,219 lb. (511–553 kg)
Maximum trailer weight	7,716 lb. (3,500 kg)	7,716 lb. (3,500 kg)
Maximum unbraked trailer weight	1,653 lb. (750 kg)	1,653 lb. (750 kg)
Maximum tongue weight	551 lb. (250 kg)	551 lb. (250 kg)
Maximum roof load	165 lb. (75 kg)	165 lb. (75 kg)