



SLR 722S Roadster - Specification

Performance		
Top Speed	335 / 208	km/h / mph
0-100 km/h	3.7	s
0-200 km/h	10.6	s

Powertrain		
Type Number		
Cylinder Arrangement	V8	
Cylinder Angle	90	degrees
Power Output	478 / 650	kW / PS
@	6500	rpm
Max. Torque	820 / 605	Nm / lb.ft
@	4000	rpm
Engine Capacity	5439 / 331.9	cc / in ³
Valves / Cylinder	3	
Bore	97.0 / 3.82	mm / inches
Stroke	92.0 / 3.62	mm / inches
Compression Ratio	8.8 : 1	
Engine Weight	232.0 / 511.8	kg / lb
Silencer Capacity	19.6	litres
Supercharger Type	Lysholm-type twin-screw	
Supercharger Boost	0.9 / 13	bar / psi
Supercharger Speed	23,000	rev / minute
Gearbox Type	5-speed Automatic	
1st Gear Ratio	3.56	
2nd Gear Ratio	2.19	
3rd Gear Ratio	1.41	
4th Gear Ratio	1	
5th Gear Ratio	0.83	
Final Drive Ratio	3.06:1	

Body		
Length	4656 / 183.3	mm / inches
Width	1908 / 75.1	mm / inches
Height	1271 / 50.0	mm / inches
Wheelbase	2700 / 106.3	mm / inches
Front Track	1638 / 64.5	mm / inches
Rear Track	1569 / 61.8	mm / inches

[▼ GALLERY](#)
[INTRODUCTION](#)
[SPECIFICATION](#)
[PRESS RELEASE](#)

Turning Circle	12.2 / 40	m / ft
Luggage Capacity (VDA)	204	litres
Fuel Tank Capacity	97.6	litres
Airbrake Angle (above 60 mph)	15	degrees
Airbrake Angle (Maximum Downforce)	65	degrees
Airbrake Angle (Driver Downforce Mode)	35	degrees

Interior

Driver Airbag Capacity	64	litres
Passenger Airbag Capacity	125	litres
Steering Wheel Diameter	380 / 14.96	mm / inches
Steering Wheel Reach Adjustment	60 / 2.36	mm / inches
Steering Wheel Height Adjustment	2.7	degrees

Chassis

Front Suspension	Double Wishbone	
Rear Suspension	Double Wishbone	
Front Tyre	255/35 ZR 19	
Front Wheel	9.0 J x 19 ET 45	
Rear Tyre	295/30 ZR 19	
Rear Wheel	11.5 J x 19 ET 44	
Front Calliper Type	8-piston fixed	
Rear Calliper Type	4-piston fixed	
Front Piston diameter	28/32	mm
Rear Piston diameter	28/30	mm
Front Brake Disc Type	Internally ventilated	
Rear Brake Disc Type	Solid	
Front Brake Disc diameter	390 / 15.35	mm / inches
Rear Brake Disc diameter	360 / 14.17	mm / inches
Front Brake Disc Thickness	36 / 1.46	mm / inches
Rear Brake Disc Thickness	26 / 1.02	mm / inches
Turns Lock-to-Lock	2.2	
Turning Circle	12.2 / 40	m / ft

<< Less