



Sixty years
of innovative
thinking.
Specified.

[Change View](#)

Equipment Levels

Standard and Options

Technical data

Accessories



TiD4 (160) Aut

TiD4 (160) Man

Turbo4 (220) Aut

Engine specifications

[> View engine curve](#)
[> View engine curve](#)
[> View engine curve](#)

Engine description	Diesel. 4 cylinders (in-line). Transverse. Alloy engine head. Cast iron engine block. Double overhead camshaft. 16 valves. Turbo. Engine management Motronic. Maintenance-free particulate filter. Dual-mass flywheel. Common rail, direct and multiple injection.	Diesel. 4 cylinders (in-line). Transverse. Alloy engine head. Cast iron engine block. Double overhead camshaft. 16 valves. Turbo. Engine management Motronic. Maintenance-free particulate filter. Dual-mass flywheel. Common rail, direct and multiple injection.	Petrol. 4 cylinders (in-line). Transverse. All-alloy engine. Double overhead camshaft 16 valves. Twin-scroll turbocharger. Engine management Motronic. Direct injection. Coil-on-plug ignition.
Drive train	Front wheel drive	Front wheel drive	Front wheel drive
Transmission	Automatic 6-speed	Manual 6-speed	Automatic 6-speed
Displacement (dm ³)	1956	1956	1998
Bore/Stroke (mm)	83.0 / 90.4	83.0 / 90.4	86.0 / 86.0
Max. Torque (Nm at r/min)	350 @ 1750	350 @ 1750	350 @ 2500
Recommended fuel (octane)	Diesel.	Diesel.	95
Max. Power (kW (hp) at r/min)	117 (160) @ 4000	117 (160) @ 4000	161 (220) @ 5300
Top speed (km/h)	209	215	235
0-100 km/h (sec)	10.1	9.9	8.5
80-120 km/h fifth gear (sec)		11.9	
Fuel Consumption (l/100 km)*	9.3 / 5.3 / 6.8	6.9 / 4.3 / 5.3	14.3 / 6.7 / 9.4
CO ₂ emis. City/highway/combined(g/km)	245 / 141 / 179	183 / 114 / 139	329 / 155 / 218
Emissions	Euro 5	Euro 5	Euro 5
Luggage compartment (dm ³)	515	515	515
Fuel tank capacity (l)	70	70	70
Max trailer load (kg)	1800	1700	1800
Max total weight (kg)	2280	2170	2280
Kerb weight (kg)	1750-1915	1725-1805	1750-1910
Brakes	Brake discs, ventilated front	Brake discs, ventilated front	Brake discs, ventilated front and rear
Brake size, front/rear (mm)	296 / 292	296 / 292	321 / 315
Steering	Power-assisted (hydraulic) rack and pinion.	Power-assisted (hydraulic) rack and pinion.	Power-assisted (hydraulic) rack and pinion.
Front suspension	McPherson struts, coil springs, gas-hydraulic shock absorbers, anti-roll bar.	McPherson struts, coil springs, gas-hydraulic shock absorbers, anti-roll bar.	McPherson struts, coil springs, gas-hydraulic shock absorbers, anti-roll bar.
Rear suspension	4-link axle, coil springs, gas-hydraulic shock absorbers, anti-roll bar	4-link axle, coil springs, gas-hydraulic shock absorbers, anti-roll bar	Linked H-arm axle, coil springs, gas-hydraulic shock absorbers, anti-roll bar
	*City/highway/Combined driving cycle, according to the 1999/100 EC directive.	*City/highway/Combined driving cycle, according to the 1999/100 EC directive.	*City/highway/Combined driving cycle, according to the 1999/100 EC directive.

